



Water Coolers

OASIS INTERNATIONAL

AQUA POINTE™

SPORTS BOTTLE FILLER

MWSBF, MW8SBF, MW12SBF

Suggested Specification

Model MW8SBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water. Model MW12SBF shall deliver 12.0 gph of 50°F water at 90°F ambient and 80°F inlet water. Model MWSBF is a non-refrigerated Bottle Filler and delivers ambient water. Key AquaPointe bottle filler molded components contain Freshield, WHICH UTILIZES a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discoloration, odors and degradation. Basin shall be designed to eliminate splashing and standing water. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1 and ADA. Shall be listed by Underwriters' Laboratories to U.S. and Canadian standards. Shall comply with ANSI/NSF 61.

Model

MW8SBF delivers 8.0 gallons of chilled drinking water per hour.

MW12SBF delivers 12.0 gallons of chilled drinking water per hour.

MWSBF is a non-refrigerated bottle filler. These models satisfy CABO/ANSI A117.1.

Standard Features


- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Waterways are Lead-free in Materials & Construction
- > Heavy Duty steel frame
- > Product Certified by NSF to NSF/ANSI Standard 61, including AB1953; except for the Green Filter System, which has been tested by independent laboratories to the NSF Standard 42, and 53, but not certified by NSF
- > High Efficiency cooling tank and coil
- > Refrigerant R-134a

Finishes

- > Standard cabinet finish: Brushed Stainless Steel
- > Optional cabinet finish: Regency Bronze

Options (at additional cost)

- > Ultra Violet filtration
- > Oasis Green Filtration System



GREEN FILTRATION SYSTEM



Installation

- > Prior to roughing, consult with local, state and federal codes for proper mounting height
- > Shipped with complete instructions and wall mounting bracket
- > Removable front panels allow for easy access to filtration and refrigeration unit



ADA Compliant for reach ranges. These models meet guidelines for children's (ages 5 and up) accessibility providing the floor to button height is less than 40 inches and proper clear floor space is provided for frontal approach.



Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Product Certified to NSF/ANSI Standard 61 and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953). Units incorporating the Green Filter option are not NSF approved. However, the Green Filter has been independently tested to the NSF standards 42 and 53.

Models covered by this specification comply with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards.



Freshield



Model	50° F Drinking Water 90° F Ambient Air Temp*		115 Volts, 60 HZ			Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Compr. HP	Full Load Amps	Rated Watts		
MWSBF						Yes	26 Lbs.
MW8SBF	8.0	8.0	1/5	4.6	340	Yes	78 Lbs.
MW12SBF	12.0	12.0	1/5	8.7	620	Yes	78 Lbs.

*Industry Standard Rating Condition 80° F inlet water temperature.

Specifications subject to change without notice

